

## 2 Megapixel IR Vandal Dome



### KEY FEATURES

- Real-time Streaming @ Full HD
- Privacy masking & True Day & Night (ICR)
- Smart IR LED
- Vandal Proof Casing, IP66
- Supports Micro SD card

### Image

Sensor	1/2.8", CMOS progressive scan
Video Compression	H.264, MJPEG
Max. Resolution	1920 × 1080
Resolution Support	2MP (1080P)@30fps 720P @30fps, D1 @25fps
Lens	2.8~12 mm, F1.4
Angle of View (H)	103°(wide) ~ 30.8°(tele)
Shutter	Auto/Manual, 1/6~1/8000 s
Day & Night	ICR
Min. illumination	Color: 0.06 lux BW : 0.03 lux (F1.4)
Gain Control	Auto/manual
S/N	>52dB
IR LEDs	1x Smart IR LED, Range: 30m

### Functions

9:16 Corridor Mode	Support
Video Streaming	Dual
Local Storage	Yes, (Micro SD Supported)
FTP Upload	Yes
OSD	Up to 8 OSDs
Zoom/Focus	Manual
Privacy Mask	Up to 4 areas

### Audio

Audio Compression	G.711
Two-way Communication	Support

### Network

Max. Connections	5
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, QoS, NTP, FTP, HTTP, HTTPS, SNMP, SIP
DDNS	Yes (Mycloud)
Remote Access Client	Ezstation, Web Client
Open IP Protocol	Yes, ONVIF
Integration	IMOS, API
Network	10M/100M Base-TX Ethernet

## 2 Megapixel IR Vandal Dome

### Interface

Audio I/O	3.5 mm audio interface, In (2.0Vp-p, 35Kohms) / Out (2.0Vp-p, 600ohms)
Alarm I/O	1 / 1

### Mechanical

Dimensions	Φ149 x 105 (H) mm
Weight	0.75 Kg

### Electrical

Power Source	12 VDC, PoE (IEEE802.3 af)
Power Consumption	3.5 W (IR on: 5.5 W)

### Environmental

Operating Temperature	-30°C ~ +60°C
Operating Humidity	≤ 90% RH (non-condensing)
Ingress Protection	IP66
Vandal Resistant	IK10