

## 5 Megapixel IR Mini Fixed Bullet Camera



### KEY FEATURES

- 30fps @ 4MP High Resolution
- H.265 Video Compression
- True Day & Night (ICR), Smart IR LED
- Powerful WDR, Corridor Mode & ROI
- IP67 Ingress protection

### Image

Sensor	1/2.7" CMOS, Progressive Scan
Video Compression	Ultra H.265, H.265, H.264, MJPEG
Max. Resolution	5MP (2880 x 1620)
Resolution Support	5MP (2880 x 1620) @ 30fps 4MP (2560 x 1440) @ 30fps 3MP (2304 x 1296) @ 30fps 1080P @ 30fps
Shutter Speed	Auto/Manual, 1~1/100000 s
Lens	4mm, F1.6 (6mm optional)
Angle of View (H)	91.2°
Min. Illumination	Color: 0.0053 Lux (AGC ON), BW: 0 Lux (IR ON)
Day & Night	ICR
S/N	>56dB
IR LED	Smart IR LED Range: 80m

### Functions

Video Streaming	Triple
9:16 Corridor Mode	Yes
FTP Upload	Yes
Digital Noise Reduction	2D/3D-DNR
Privacy Mask	Up to 4 areas
Motion Detection	Yes
ROI	Up to 8 areas
OSD	Up to 8 OSDs
HLC/BLC	Yes
Local Storage	Yes (Micro SD, up to 256GB)
WDR	120dB
Defog	Digital

### Smart Analytics

Motion Detection, Tampering Detection, Audio Detection, Smart Intrusion Prevention (Cross Line, Enter Area, Leave Area, Intrusion), People Counting, People Flow Counting, Crowd Density Monitoring, Face Capture

### Network

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH
Remote Access Client	GuardStation, Web Client, uMobile
Open IP Protocol	ONVIF
Network	10M/100M Base-TX Ethernet

---

## 5 Megapixel IR Mini Fixed Bullet Camera

### Interface

Alarm I/O	1 / 1
Built-in Mic	2

### Electrical

Power Source	12 VDC, PoE (IEEE802.3 af)
Power Consumption	Max. 7W

### Environmental

Operating Temperature	-30°C ~ +60°C
Operating Humidity	≤ 95% RH (non-condensing)
Ingress Protection	IP67

### Mechanical

Dimensions (W x D x H)	74 x 206 x 74 mm
Weight	0.51Kg

Draft